Scotsman[®] Ice Systems

Subcooled Scale Ice Machine -Vertical Evaporator 2000 / 3000 / 4000 Kg in 24h

ES2040

Other models in this range: ES1014 - ES4050 Compact versions: EC10 - EC15 - EC25 - EC30 - EC40 - EC50













This product qualifies for the following listings:









Features


- Evaporator: cylinder made of AISI304 stainless steel, insulation made by polyurethane foam; external finishing in stainless steel; drip-tray in ABS food-proof.
- Cover in stainless steel.
- Base in alluminium alloy (Peralluman).
- Rotating shaft made of stainless steel with IGLIDUR bush.
- Ice scraper made of stainless steel with self-lubricating stainless steel bearings.
- Drive motor with direct connection with gear reducer.
- Three phase water pump; Water level sensor on water distributor (to be connected to level contactor).
- Floating valve for water supply; Overflow connection on the base; Drip pan in ABS plastic
- Thermostatic expansion valve with external pressure regulation.
- Salt dosing pump.

Accessories included, to be installed on site:

- Mechanical filter on water pipe supply
- Drive motor ammetric protection for electrical panel

Electrical control board (accessory QEES204002600):

- Epoxy painted box IP55
- Power switch
- Emergency push button
- Working and Alarm lightings
- Trasformer for contactors
- Power contactors with thermal protections
- Timers for drive motor, water pump, water level sensor and compressor pump-down
- Water level relais
- Drive motor ammetric protection
- Inverter for drive motor supply
- Terminal board for electrical connections





to -9°Celsius, they are very dry, containing less than 2% residual water. Scales look like fragments of glass, have an irregular shape and a thickness that can be adjusted from 1,2 to 2,0 mm.

Ice scales are the coldest form of ice. Formed at -5°



Residual water content 2%



[v/Hz/ph]


400/50/3+N

R 404 A


Scotsman[®] Ice Systems

Subcooled Scale Ice Machine -Vertical Evaporator 2000 / 3000 / 4000 Kg in 24h

Other models in this range: ES1014 - ES4050 Compact versions: EC10 - EC15 - EC25 - EC30 - EC40 - EC50



Technical features	2000 Kg	3000 Kg	4000 Kg			
Electrical Power: KW / A	Pump 0,35 / 0,95 Drive motor 0,18 / 0,62					
Extraction rate: W	12.000	18.000	21.500			
Evap.Temperature: °C	-26	-28	-28			
Volume refrigeration system	30					
Max pressure PS (Dir. 97/23/CE)	17,50 bar					
Category PED (Dir. 97/23/CE)	II					
Refrigerant charge Kg	30					



	•			P	
	[V/Hz/ph]	[W] [A]	[kg] [lbs]	[kg] [lbs]	[shipping size mm]
ES2040	400/50/3+N	0,55W 1,60A	300 660	400 880	1360x980x1670 (2,23 m³)

Water supply type: fresh

Scotsman Ice Systems

CONTACT POINTS:

Europe Scotsman Europe-Frimont S.p.A. Ph/Fax +39-0293960208 / 0293960201 scotsman.europe@frimont.it Paolo Moro

Middle East & N. Africa Scotsman-Frimont Regional Office (MEnA) Ph/Fax +97-16 5262944 / 165262946 m.dawood@frimont.ae fernando.m@frimont.ae

Asia and Pacific Scotsman Industries (S) PTE. L.T.D. Ph/Fax +65-67385393 / 67381959 scotsman@scotsman.com.sg Andrea Tronci

South Africa

Scotsman SA (Pty) Ltd - Ice Systems (Pty) Ltd Ph +27-0105900609 / 0877200245/67/78 Fax: +27-118264123 / 0866340803 stuart@scotsmansa.co.za - jennifer@scotsman.co.za

Scotsman Group India Ph/Fax : +91-1244002459 / direct 9560072459 david.owen@scotsman.com.sg

Scotsman España, S.L.U. c/ Galapagar, 12 Ph/Fax +34-911109796 / 916337423

Scotsman Ice Systems (Shanghai) Ph/Fax: +86-2161313200 / 2161313330 scotsman.shanghai@scotsman-china.com Andrew Clayton

6/201